Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Intersil
EL5611IREZ

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Data Sheet | August 3, 2005 | FN7355.1

60MHz Rail-to-Rail Input-Output V_{COM} Amplifiers

The EL5611 and EL5811 are low power, high voltage rail-to-rail input-output amplifiers targeted primarily at V_{COM} applications in TFT-LCD displays. The EL5611 contains six amplifiers, and the EL5811 contains eight amplifiers. Operating on supplies ranging from 5V to 15V, while consuming only 2.5mA per amplifier, the EL5611 and EL5811 have a bandwidth of 60MHz (-3dB). They also provide common mode input ability beyond the supply rails, as well as rail-to-rail output capability. This enables these amplifiers to offer maximum dynamic range at any supply voltage.

The EL5611 and EL5811 also feature fast slewing and settling times, as well as a high output drive capability of 65mA (sink and source). In addition to V_{COM} applications, these features make these amplifiers ideal for high speed filtering and signal conditioning application. Other applications include battery power, portable devices, and anywhere low power consumption is important.

The EL5611 is available in 8-pin MSOP and 8-pin HMSOP packages. The EL5811 is available in space-saving 28-pin HTSSOP packages.These amplifiers operate over a temperature range of -40°C to +85°C.

Features

- 60MHz -3dB bandwidth
- Supply voltage = 4.5V to 16.5V
- Low supply current (per amplifier) = 2.5mA
- High slew rate = 75V/µs
- Unity-gain stable
- Beyond the rails input capability
- Rail-to-rail output swing
- ±180mA output short current
- Pb-Free plus anneal available (RoHS compliant)

Applications

- TFT-LCD panels
- V_{COM} amplifiers
- Drivers for A-to-D converters
- Data acquisition
- Video processing
- Audio processing
- Active filters
- Test equipment
- Battery-powered applications
- Portable equipment

Ordering Information

PART NUMBER	PACKAGE	TAPE & REEL	PKG. DWG. #
EL5611IRE	24-Pin HTSSOP	-	MDP0048
EL5611IRE-T7	24-Pin HTSSOP	7”	MDP0048
EL5611IRE-T13	24-Pin HTSSOP	13”	MDP0048
EL5811IREZ (See Note)	28-Pin HTSSOP (Pb-free)	-	MDP0048
EL5811IREZ-T7 (See Note)	28-Pin HTSSOP (Pb-free)	7”	MDP0048
EL5811IREZ-T13 (See Note)	28-Pin HTSSOP (Pb-free)	13”	MDP0048
EL5811IREZ (See Note)	28-Pin HTSSOP (Pb-Free)	-	MDP0048
EL5811IREZ-T7 (See Note)	28-Pin HTSSOP (Pb-Free)	7”	MDP0048

Ordering Information (Continued)

PART NUMBER	PACKAGE	TAPE & REEL	PKG. DWG. #
EL5811IREZ-T13 (See Note)	28-Pin HTSSOP (Pb-Free)	13”	MDP0048

NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.
1-888-INTERSIL or 1-888-468-3774 | Intersil (and design) is a registered trademark of Intersil Americas Inc.
Copyright Intersil Americas Inc. 2004, 2005. All Rights Reserved
All other trademarks mentioned are the property of their respective owners.

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Pinouts

EL5611
(24-PIN HTSSOP)
TOP VIEW



EL5811
(28-PIN HTSSOP)
TOP VIEW



Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Absolute Maximum Ratings (T_A = 25°C)

Supply Voltage between V_S+ and V_S- . . . . . +18V
Input Voltage . . . . . V_S- - 0.5V, V_S +0.5V
Maximum Continuous Output Current 65mA
Maximum Die Temperature . . . . . +125°C
Storage Temperature . . . . . -65°C to +150°C
Ambient Operating Temperature . . . . . -40°C to +85°C
Power Dissipation . . . . . See Curves

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

IMPORTANT NOTE: All parameters having Min/Max specifications are guaranteed. Typical values are for information purposes only. Unless otherwise noted, all tests are at the specified temperature and are pulsed tests, therefore: $T_J = T_C = T_A$

Electrical Specifications

V_S+ = +5V, V_S- = -5V, R_L = 1kΩ to 0V, T_A = 25°C, Unless Otherwise Specified

PARAMETER	DESCRIPTION	CONDITIONS	MIN	TYP	MAX	UNIT
INPUT CHARACTERISTICS						
V_{OS}	Input Offset Voltage	V_{CM} = 0V		3	15	mV
TCV_{OS}	Average Offset Voltage Drift (Note 1)			7		µV/°C
I_B	Input Bias Current	V_{CM} = 0V		2	60	nA
R_{IN}	Input Impedance			1		GΩ
C_{IN}	Input Capacitance			2		pF
CMIR	Common-Mode Input Range		-5.5		+5.5	V
CMRR	Common-Mode Rejection Ratio	for V_{IN} from -5.5V to 5.5V	50	70		dB
A_{VOL}	Open-Loop Gain	-4.5V ≤ V_{OUT} ≤ 4.5V	62	70		dB
OUTPUT CHARACTERISTICS						
V_{OL}	Output Swing Low	I_L = -5mA		-4.92	-4.85	V
V_{OH}	Output Swing High	I_L = 5mA	4.85	4.92		V
I_{SC}	Short-Circuit Current			±180		mA
I_{OUT}	Output Current			±65		mA
POWER SUPPLY PERFORMANCE						
PSRR	Power Supply Rejection Ratio	V_S is moved from ±2.25V to ±7.75V	60	80		dB
I_S	Supply Current (Per Amplifier)	No load		2.5	3.75	mA
DYNAMIC PERFORMANCE						
SR	Slew Rate (Note 2)	-4.0V ≤ V_{OUT} ≤ 4.0V, 20% to 80%		75		V/µs
t_S	Settling to +0.1% (A_V = +1)	(A_V = +1), V_O = 2V step		80		ns
BW	-3dB Bandwidth			60		MHz
GBWP	Gain-Bandwidth Product			32		MHz
PM	Phase Margin			50		°
CS	Channel Separation	f = 5MHz		110		dB
d_G	Differential Gain (Note 3)	R_F = R_G = 1kΩ and V_{OUT} = 1.4V		0.17		%
d_P	Differential Phase (Note 3)	R_F = R_G = 1kΩ and V_{OUT} = 1.4V		0.24		°

NOTES:

1. Measured over operating temperature range.
2. Slew rate is measured on rising and falling edges.
3. NTSC signal generator used.

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Electrical Specifications

V_S+ = +5V, V_S- = 0V, R_L = 1kΩ to 2.5V, T_A = 25°C, Unless Otherwise Specified

PARAMETER	DESCRIPTION	CONDITION	MIN	TYP	MAX	UNIT
INPUT CHARACTERISTICS						
V_{OS}	Input Offset Voltage	V_{CM} = 2.5V		3	15	mV
TCV_{OS}	Average Offset Voltage Drift (Note 4)			7		µV/°C
I_B	Input Bias Current	V_{CM} = 2.5V		2	60	nA
R_{IN}	Input Impedance			1		GΩ
C_{IN}	Input Capacitance			2		pF
CMIR	Common-Mode Input Range		-0.5		+5.5	V
CMRR	Common-Mode Rejection Ratio	for V_{IN} from -0.5V to 5.5V	45	66		dB
A_{VOL}	Open-Loop Gain	0.5V ≤ V_{OUT} ≤ 4.5V	62	70		dB
OUTPUT CHARACTERISTICS						
V_{OL}	Output Swing Low	I_L = -5mA		80	150	mV
V_{OH}	Output Swing High	I_L = 5mA	4.85	4.92		V
I_{SC}	Short-circuit Current			±180		mA
I_{OUT}	Output Current			±65		mA
POWER SUPPLY PERFORMANCE						
PSRR	Power Supply Rejection Ratio	V_S is moved from 4.5V to 15.5V	60	80		dB
I_S	Supply Current (Per Amplifier)	No load		2.5	3.75	mA
DYNAMIC PERFORMANCE						
SR	Slew Rate (Note 5)	1V ≤ V_{OUT} ≤ 4V, 20% to 80%		75		V/µs
t_S	Settling to +0.1% (A_V = +1)	(A_V = +1), V_O = 2V step		80		ns
BW	-3dB Bandwidth			60		MHz
GBWP	Gain-Bandwidth Product			32		MHz
PM	Phase Margin			50		°
CS	Channel Separation	f = 5MHz		110		dB
d_G	Differential Gain (Note 6)	R_F = R_G = 1kΩ and V_{OUT} = 1.4V		0.17		%
d_P	Differential Phase (Note 6)	R_F = R_G = 1kΩ and V_{OUT} = 1.4V		0.24		°

NOTES:

4. Measured over operating temperature range.
5. Slew rate is measured on rising and falling edges.
6. NTSC signal generator used.

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Electrical Specifications

V_S+ = +15V, V_S- = 0V, R_L = 1kΩ to 7.5V, T_A = 25°C, Unless Otherwise Specified

PARAMETER	DESCRIPTION	CONDITION	MIN	TYP	MAX	UNIT
INPUT CHARACTERISTICS						
V_{OS}	Input Offset Voltage	V_{CM} = 7.5V		3	15	mV
TCV_{OS}	Average Offset Voltage Drift (Note 7)			7		µV/°C
I_B	Input Bias Current	V_{CM} = 7.5V		2	60	nA
R_{IN}	Input Impedance			1		GΩ
C_{IN}	Input Capacitance			2		pF
CMIR	Common-Mode Input Range		-0.5		+15.5	V
CMRR	Common-Mode Rejection Ratio	for V_{IN} from -0.5V to 15.5V	53	72		dB
A_{VOL}	Open-Loop Gain	0.5V ≤ V_{OUT} ≤ 14.5V	62	70		dB
OUTPUT CHARACTERISTICS						
V_{OL}	Output Swing Low	I_L = -5mA		80	150	mV
V_{OH}	Output Swing High	I_L = 5mA	14.85	14.92		V
I_{SC}	Short-circuit Current			±180		mA
I_{OUT}	Output Current			±65		mA
POWER SUPPLY PERFORMANCE						
PSRR	Power Supply Rejection Ratio	V_S is moved from 4.5V to 15.5V	60	80		dB
I_S	Supply Current (Per Amplifier)	No load		2.5	3.75	mA
DYNAMIC PERFORMANCE						
SR	Slew Rate (Note 8)	1V ≤ V_{OUT} ≤ 14V, 20% to 80%		75		V/µs
t_S	Settling to +0.1% (A_V = +1)	(A_V = +1), V_O = 2V step		80		ns
BW	-3dB Bandwidth			60		MHz
GBWP	Gain-Bandwidth Product			32		MHz
PM	Phase Margin			50		°
CS	Channel Separation	f = 5MHz		110		dB
d_G	Differential Gain (Note 9)	R_F = R_G = 1kΩ and V_{OUT} = 1.4V		0.16		%
d_P	Differential Phase (Note 9)	R_F = R_G = 1kΩ and V_{OUT} = 1.4V		0.22		°

NOTES:

7. Measured over operating temperature range
8. Slew rate is measured on rising and falling edges
9. NTSC signal generator used

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Typical Performance Curves



FIGURE 1. INPUT OFFSET VOLTAGE DISTRIBUTION



FIGURE 2. INPUT OFFSET VOLTAGE DRIFT



FIGURE 3. INPUT OFFSET VOLTAGE vs TEMPERATURE



FIGURE 4. INPUT BIAS CURRENT vs TEMPERATURE



FIGURE 5. OUTPUT HIGH VOLTAGE vs TEMPERATURE



FIGURE 6. OUTPUT LOW VOLTAGE vs TEMPERATURE

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Typical Performance Curves (Continued)



FIGURE 7. OPEN-LOOP GAIN vs TEMPERATURE



FIGURE 8. SLEW RATE vs TEMPERATURE



FIGURE 9. SUPPLY CURRENT PER AMPLIFIER vs SUPPLY VOLTAGE



FIGURE 10. SUPPLY CURRENT PER AMPLIFIER vs TEMPERATURE



FIGURE 11. DIFFERENTIAL GAIN



FIGURE 12. DIFFERENTIAL PHASE

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Typical Performance Curves (Continued)



FIGURE 13. HARMONIC DISTORTION vs V_{OP-P}



FIGURE 14. OPEN LOOP GAIN AND PHASE



FIGURE 15. FREQUENCY RESPONSE FOR VARIOUS R_L



FIGURE 16. FREQUENCY RESPONSE FOR VARIOUS C_L



FIGURE 17. CLOSED LOOP OUTPUT IMPEDANCE



FIGURE 18. MAXIMUM OUTPUT SWING vs FREQUENCY

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Typical Performance Curves (Continued)



FIGURE 19. CMRR



FIGURE 20. PSRR



FIGURE 21. INPUT VOLTAGE NOISE SPECTRAL DENSITY



FIGURE 22. CHANNEL SEPARATION



FIGURE 23. SMALL-SIGNAL OVERSHOOT vs LOAD CAPACITANCE



FIGURE 24. SETTLING TIME vs STEP SIZE

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Typical Performance Curves (Continued)



FIGURE 25. LARGE SIGNAL TRANSIENT RESPONSE



FIGURE 26. SMALL SIGNAL TRANSIENT RESPONSE

Pin Descriptions

EL5611	EL5811	NAME	FUNCTION	EQUIVALENT CIRCUIT
1, 5, 9, 14, 20, 23	4, 5, 10, 11, 17, 18, 25, 26	VOUTx	Amplifiers output	 CIRCUIT 1
2, 3, 6, 7, 9, 10, 15, 16, 21, 22	2, 3, 6, 7, 8, 9, 12. 13, 15, 16, 19, 20, 23, 24, 27, 28	VINx	Amplifiers input	 CIRCUIT 2
8, 24	1, 14	VS+	Positive power supply	
24, 17	21, 22	VS-	Negative power supply	
12, 13		NC	Not connected	

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Applications Information

Product Description

The EL5611 and EL5811 voltage feedback amplifiers are fabricated using a high voltage CMOS process. They exhibit rail-to-rail input and output capability, are unity gain stable and have low power consumption (2.5mA per amplifier). These features make the EL5611, and EL5811 ideal for a wide range of general-purpose applications. Connected in voltage follower mode and driving a load of 1kΩ, the EL5611 and EL5811 have a -3dB bandwidth of 60MHz while maintaining a 75V/µs slew rate. The EL5611 a six channel amplifier, and the EL5811 an 8 channel amplifier.

Operating Voltage, Input, and Output

The EL5611and EL5811 are specified with a single nominal supply voltage from 5V to 15V or a split supply with its total range from 5V to 15V. Correct operation is guaranteed for a supply range of 4.5V to 16.5V. Most EL5611 and EL5811 specifications are stable over both the full supply range and operating temperatures of -40°C to +85°C. Parameter variations with operating voltage and/or temperature are shown in the typical performance curves.

The input common-mode voltage range of the EL5611 and EL5811 extends 500mV beyond the supply rails. The output swings of the EL5611 and EL5811 typically extend to within 100mV of positive and negative supply rails with load currents of 5mA. Decreasing load currents will extend the output voltage range even closer to the supply rails. Figure 27 shows the input and output waveforms for the device in the unity-gain configuration. Operation is from ±5V supply with a 1kΩ load connected to GND. The input is a $10V_{P-P}$ sinusoid. The output voltage is approximately $9.8V_{P-P}$.

V_S = ±5V, T_A = 25°C, A_V = 1, V_{IN} = $10V_{P-P}$



FIGURE 27. OPERATION WITH RAIL-TO-RAIL INPUT AND OUTPUT

Short Circuit Current Limit

The EL5611 and EL5811 will limit the short circuit current to ±180mA if the output is directly shorted to the positive or the negative supply. If an output is shorted indefinitely, the power dissipation could easily increase such that the device may be damaged. Maximum reliability is maintained if the output continuous current never exceeds ±65mA. This limit is set by the design of the internal metal interconnects.

Output Phase Reversal

The EL5611 and EL5811 are immune to phase reversal as long as the input voltage is limited from V_S- -0.5V to V_S+ +0.5V. Figure 28 shows a photo of the output of the device with the input voltage driven beyond the supply rails. Although the device's output will not change phase, the input's overvoltage should be avoided. If an input voltage exceeds supply voltage by more than 0.6V, electrostatic protection diodes placed in the input stage of the device begin to conduct and overvoltage damage could occur.

V_S = ±2.5V, T_A = 25°C, A_V = 1, V_{IN} = $6V_{P-P}$



FIGURE 28. OPERATION WITH BEYOND-THE-RAILS INPUT

Power Dissipation

With the high-output drive capability of the EL5611 and EL5811 amplifiers, it is possible to exceed the 125°C 'absolute-maximum junction temperature' under certain load current conditions. Therefore, it is important to calculate the maximum junction temperature for the application to determine if load conditions need to be modified for the amplifier to remain in the safe operating area.

The maximum power dissipation allowed in a package is determined according to:

$$P_{DMAX} = \frac{T_{JMAX} - T_{AMAX}}{\Theta_{JA}}$$

where:

- T_{JMAX} = Maximum junction temperature
- T_{AMAX} = Maximum ambient temperature
- Θ_{JA} = Thermal resistance of the package
- P_{DMAX} = Maximum power dissipation in the package

The maximum power dissipation actually produced by an IC is the total quiescent supply current times the total power supply voltage, plus the power in the IC due to the loads, or:

$$P_{DMAX} = \Sigma i[V_S \times I_{SMAX} + (V_S + - V_{OUT}i) \times I_{LOAD}i]$$

Distributor of Intersil : Excellent Integrated System Limited
Datasheet of EL5611IREZ - IC OPAMP GP 32MHZ RRO 24HTSSOP
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

when sourcing, and:

$$P_{DMAX} = \Sigma i[V_S \times I_{SMAX} + (V_{OUT}i - V_S\text{-}) \times I_{LOAD}i]$$

when sinking,

where:

- i = 1 to 6 for EL5611 and 1 to 8 for EL5811
- V_S = Total supply voltage
- I_{SMAX} = Maximum supply current per amplifier
- $V_{OUT}i$ = Maximum output voltage of the application
- $I_{LOAD}i$ = Load current

If we set the two P_{DMAX} equations equal to each other, we can solve for $R_{LOAD}i$ to avoid device overheat. Figures 29 and 30 provide a convenient way to see if the device will overheat. The maximum safe power dissipation can be found graphically, based on the package type and the ambient temperature. By using the previous equation, it is a simple matter to see if P_{DMAX} exceeds the device's power derating curves. To ensure proper operation, it is important to observe the recommended derating curves shown in Figures 29 & 30.



FIGURE 29. PACKAGE POWER DISSIPATION vs AMBIENT TEMPERATURE



FIGURE 30. PACKAGE POWER DISSIPATION vs AMBIENT TEMPERATURE

Unused Amplifiers

It is recommended that any unused amplifiers in a dual and a quad package be configured as a unity gain follower. The inverting input should be directly connected to the output and the non-inverting input tied to the ground plane.

Power Supply Bypassing and Printed Circuit Board Layout

The EL5611 and EL5811 can provide gain at high frequency. As with any high-frequency device, good printed circuit board layout is necessary for optimum performance. Ground plane construction is highly recommended, lead lengths should be as short as possible and the power supply pins must be well bypassed to reduce the risk of oscillation. For normal single supply operation, where the V_S- pin is connected to ground, a 0.1µF ceramic capacitor should be placed from V_S+ to pin to V_S- pin. A 4.7µF tantalum capacitor should then be connected in parallel, placed in the region of the amplifier. One 4.7µF capacitor may be used for multiple devices. This same capacitor combination should be placed at each supply pin to ground if split supplies are to be used.

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.
Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com