

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)

[66432-124](#)



For any questions, you can email us directly:

sales@integrated-circuit.com




Copyright FCI.

PRODUCT NO.
SEE TABLE



mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY		FCI		www.fciconnect.com	
ltr	ecm no	dr	date	linear	.X ± 0.10	projection	title	product family	code	size	dwg no
J	V22169	MSC	1992-05-21	near	.XX ± 0.05	INCH/MM	DUAL POLARIZED QUICKIE II LOW PROFILE	QUICKIE	NT		
K	N05-0368	GUL	2005-12-27	angles	.XXX ±	1:1					
L	N09-0400	AZH	2010-01-18	br	± 2						
				enr	GuLing 12/27/05						
				enr	TaoDeniel 12/27/05						
				chr	TaoDeniel 12/27/05						
				appd	Jason Zhou 12/27/05						
sheet index	revision sheet	L	1-2								

1					2		3		
PRODUCT NO.	SIZE	DIM. L	DIM. S	DIM. C	DASH NO	STYLE	COVER ORIENTATION	POLARIZATION	STRAIN RELIEF
66432-X10/X10LF	2X5	17.27	13.21	10.16	-0XX	THRU	DUAL ENTRY	DUAL POL.	YES
-X14/X14LF	2X7	22.35	18.29	15.24	-1XX	THRU	DUAL ENTRY	CENTER KEY & DUAL POL.	YES
-X16/X16LF	2X8	24.89	20.83	17.78	-2XX	BLIND	RIGHT	DUAL	YES
-X20/X20LF	2X10	29.97	25.91	22.86	-3XX	BLIND	RIGHT	CENTER KEY & DUAL POL.	YES
-X24/X24LF	2X12	35.05	30.99	27.94	-4XX	BLIND	LEFT	DUAL POL.	YES
-X26/X26LF	2X13	37.59	33.53	30.48	-5XX	BLIND	LEFT	CENTER KEY & DUAL POL.	YES
-X30/X30LF	2X15	42.67	38.61	35.56	-6XX	BLIND	RIGHT	CENTER KEY & DUAL POL.	NO
-X34/X34LF	2X17	47.75	43.69	40.64	-7XX	BLIND	LEFT	CENTER KEY & DUAL POL.	NO
-X40/X40LF	2X20	55.37	51.31	48.26	-8XX	DISCONTINUED			
-X44/X44LF	2X22	60.45	56.39	53.34	-9XX	DISCONTINUED			
-X50/X50LF	2X25	68.07	64.01	60.96					
66432-X60/X60LF	2X30	80.77	76.71	73.66					

COVER
ORIENTATION

NOTES:

1. TERMINAL MATERIAL: FULL HARD PHOS. BRONZE ALLOY. UNS-C51000.
2. TERMINAL PLATING: 50u"/1.27um MIN NI UNDERPLATE OVER ENTIRE TERMINAL AND 30u"/0.76um MIN Au OR GXT IN CONTACT AREA ONLY.
3. MOLDING MATERIAL: BASE & COVER-GLASS FILLED POLYESTER. FLAME RETARDANT PER UL94V-0. COLOR-BLUE.
4. CONNECTOR ASSEMBL ES PACKAGED IN TUBES.
5. THE FIRST TWO CAVITY POSITIONS AND THE LAST TWO. ARE IDENTIFIED BY NUMBER.
6. POLARIZING FEATURES ARE DESCRIBED IN TABLE.
7. MOLDING MATERIAL: STRAIN RELIEF-POLYSULFONE. FLAME RETARDANT PER UL 94V-0,COLOR-NATURAL.
8. THE POLARIZING FEATURE ON THIS END IS NON-EXISTANT ON 2X5 AND 2X7 POSITION CONNECTORS.
9. 2X5 POSITION NOT AVAILABLE WITH POLARIZATION SLOT ON CENTER KEY STYLE.
10. PRODUCT NUMBER 66432-XXX_LF LEAD FREE OPTION
11. WITH "LF" MARK, TERMINAL PLATING: 50u"/1.27um Ni UNDERPLATE OVER ENTIRE TERMINAL AND 30u"/0.76um MIN Au OR GXT IN CONTACT AREA ONLY.
12. FOR LEAD FREE P/N, THE PRODUCT MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
13. FOR LEAD FREE P/N, THE PLASTIC PART WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION.
14. PRODUCT SPEC. BUS-12-082
15. PLATING OPTIONS: MAY BE EITHER GOLD OR GXT PLATED AT MANUFACTURER'S OPTION.

tolerances unless otherwise specified				CUSTOMER COPY				www.fciconnect.com	
linear	.X ± 0.1			projection		title	DUAL POLARIZED QUICKIE II LOW PROFILE		
	.XX ± 0.05								
	.XXX ±								
angles	± 2			INCH/MM	scale	product family	QUICKIE		code
dr	Guling	12/27/05							
engr	TaoDeniel	12/27/05							
chr	TaoDeniel	12/27/05		1:1	A4	dwg no	66432		sheet
ppd	Jason Zhou	12/27/05							2 of 2

PDM: Rev:L

STATUS:Released

Printed: Apr 12, 2011