Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

FCI
HM2R10PA510FE9

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of FCI: Excellent Integrated System Limited
Datasheet of HM2R10PA510FE9 - CONN RECEPT 110POS TYPE A R/A
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com







PERFORMANCE CHARACTERISTICS

CURRENT RATING 1.5 A AT 20°C (FULLY LOADED)
1 A AT 70°C (FULLY LOADED)

RATED VOLTAGE 500V AC (CONT / CONT)

OPERATING TEMPERATURE -55°C TO 125°C

CONTACT RESISTANCE 20 MΩ MAX

INSERTION FORCE :0.75 N MAX /CONT

EXTRACTION FORCE: 0.15 N MIN /CONT

INSULATION RESISTANCE :10^4 MΩ MIN

NOTES

1. LEAD FREE INDICATOR : LF- LEAD FREE
   PERFORMANCE LEVEL INDICATION (REF DWG No. BS,C,201844,003)
2. THIS PRODUCT IS CSA APPROVED
   THIS PRODUCT IS UL RECOGNISED
3. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING: BSA,201,572001
4. THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVE AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.



Material		Spec ref	
Mat code		tolerance	projection
Heattreat			MM
Plating/Finish			

rev	ecn no	dr	date
A	[illegible]	KN	14-9-05
B	035-0893	MENO	05/06/05
C	0505-0878	Kasan	05/08/05
D	0507-0362	Kasan	05/09/07
E	0510-0101	MZ	05/10/10
-	-	-	-
07	[illegible]	RJM	09.08.01

Dr	4 2 92	J V B	size A1 / Scale 5.000
Eng			Product family MILLIPACS
Chr			Model Name HM2R10PA510F----- ECN
Appr			Model Revision REL Level

FCI	title	MPACS 5+2R RA RCP CONN TYPE A	dwg BS,C,201444,031 Rev. E
Pro/E file	catalog no	HM2R10PA510F-----	CUSTOMER DRAWING sheet 1 of 1

PDM: Rev:E STATUS:Released Printed: Mar 15, 2011