

Excellent Integrated System Limited





Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[On-Shore Technology, Inc.](#)
[OSTEV026150](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



SECTION A-A

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	20.16	30.32	40.48	50.64	60.80	70.96	81.12	91.28	101.44	111.60	121.76
Dim B	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76
TOL	±0.25					±0.35					

SIGN	DATE	DESCRIPTION	APPROVER
△		THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!	

Material

- Insulating body: Thermoplastic (UL94V-0)
- Insulating cover: Thermoplastic (UL94V-0)
- Terminal screw: Steel Cr3+ Zinc plating "-" slot type
- Terminal body(house): Brass, Ni plated
- Contact PIN: PhBz (CuSn) Sn plated
- Wire guard: Stainless Steel

Electrical cULus / IEC

- Voltage rating: 600VAC / 1000VAC
- Current rating: 55A / 76A
- Solid wire: 6-20 / 0.5-16mm²
- Stranded wire: 6-20 / 0.5-16mm²
- Torque: 10.4 Lb-In / 1.2 N.m
- Screw: M4
- Wire strip length: 13-14mm
- Withstanding Voltage: 2.2KV / 8KV
- Operating temperature: -30°C to +105°C
- Safety Approval: cULus

RoHS Compliant

PART NUMBER:

OSTEVXX6150

No. of Poles	COLOR
02 2 Poles	0: Black
03 3 Poles	2: Red
... ..	5: Green (Standard)
12 12 Poles	8: Grey

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.



ON-SHORE TECHNOLOGY, INC.

TITLE		OST EV 10.16 Series 2p-12p	
PART NO.	OSTEVXX6150	DWG NO.	OSTEVXX6150.DWG
APPROVED	CHECKED	DESIGNED	DRAWN
		Aaron 2007.12.04	Aaron 2007.12.04
SHEET: 01/01		UNIT: mm	SCALE: NONE
		REV: B	Tolerance
			X ±0.50
			XX ±0.30
			XXX ±0.10
			X* ±1°