Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

3M
HSHM-S110A1-5AP1-TG30

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of 3M: Excellent Integrated System Limited
Datasheet of HSHM-S110A1-5AP1-TG30 - CONN SOCKET HSHM 110POS 5ROW
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

3M™ MetPak™ HSHM Press-Fit Socket

2 mm Type A, 110 Signal Contacts, 5 Rows, Right Angle — HSHM Series



- Up to 5 Gb/s data rates
- Low crosstalk at high frequencies
- 50/100 Ω (single-ended /differential) impedance
- Modular/scalable format IEC 61076-4-101
- 63 mated lines per linear inch
- Mates with 3M™ MetPak™ HSHM headers
- Dual beam contact construction for high reliability
- Multi-purpose center (MPC) for keying and guidance
- End-to-end stackable with 5 row 3M™ MetPak™ CP2, HM and HSHM sockets
- See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of www.3mconnector.com for compliance information

Date Modified: October 7, 2010

Physical

Insulation Material:	High Temperature Thermoplastic (LCP)
Flammability:	UL 94V-0
Contact Material:	Copper Alloy
Plating:	See Ordering Information

Performance

Mechanical:	
Normal Force (Nominal):	0.57 N [58 g] Signal, 0.74 N [75 g] Shield
Engagement Force (Nominal):	0.32 N [33 g] Signal, 0.22 N [22 g] Shield
Separation Force (Nominal):	0.20 N [20 g] Signal, 0.20 N [20 g] Shield
Wipe (Nominal, Shortest Contact):	2.67 mm [0.105 in] Signal, 1.57 mm [0.062 in] Shield
Mate/Unmate Cycles:	250
Application:	This module is not suitable for stand-alone use. (Refer to IEC-61076-4-101)
Electrical:	
Data Rate:	5 Gb/s
Characteristic Impedance:	50 Ω Single-ended, 100 Ω Differential
Current Rating (Fully Loaded):	1 A @ 70°C Signal
Insulation Resistance:	10^4 MΩ @ 100 V_{DC}
Withstanding Voltage:	750 V_{RMS}

Environmental

Temperature Rating:	-55° C to 125° C

UL File No.: E68080

MetPak is a trademark of 3M Company.

Distributor of 3M: Excellent Integrated System Limited
Datasheet of HSHM-S110A1-5AP1-TG30 - CONN SOCKET HSHM 110POS 5ROW
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

3M™ MetPak™ HSHM Press-Fit Socket

2 mm Type A, 110 Signal Contacts, 5 Rows, Right Angle — HSHM Series





mm
(Inch)

Tolerance Unless Noted			
	0	0.0	0.00
mm	±3	±0.3	±0.13

[ ] Dimensions for Reference Only

Ordering Information

HSHM-S110AX - 5AP1- XXXXX

High Speed Option:
1 = Row differential applications
4 = Coaxial and column differential applications

Plating µm [µ"]:

TG30 = 0.76 [30] Min. Au Contact Area
2.54 [100] Min. SnPb Terminal Area (RIA C2 & E2 apply)
1.27 [50] Min. Ni All over
Standard Option

TG30L = 0.76 [30] Min. Au Contact Area, Lubricated
2.54 [100] Min. SnPb Terminal Area (RIA C2 & E2 apply)
1.27 [50] Min. Ni All over
Typically higher make order quantities as compared to TG30.

TG50 = 1.27 [50] Min. Au Contact Area, Lubricated
2.54 [100] Min. SnPb Terminal Area (RIA C2 & E2 apply)
1.27 [50] Min. Ni All over
Non-Standard Option (Available with longer lead times and higher make order quantities, MOQ)

3M
Electronic Solutions Division
Interconnect Solutions
http://www.3Mconnector.com

3M is a trademark of 3M Company.
For technical, sales or ordering information call
800-225-5373

Distributor of 3M: Excellent Integrated System Limited
Datasheet of HSHM-S110A1-5AP1-TG30 - CONN SOCKET HSHM 110POS 5ROW
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

3M™ MetPak™ HSHM Press-Fit Socket

2 mm Type A, 110 Signal Contacts, 5 Rows, Right Angle — HSHM Series



Recommended PCB hole mounting pattern for coaxial, column differential and stripline applications.



Recommended PCB hole mounting pattern for row differential applications.
(Same geometry as above without the ground vias.)

Hole Plating Table mm [in.]			
Finsihed Hole Dia. "D"	**Cu. Thickness**	**SnPb Thickness**	**Drilled Hole Dia.**
0.457 - 0.559 [.0180 - .0220]	0.025 - 0.045 [.0010 - .0018]	0.008 -0.018 [.0003 - .0007]	0.584 - 0.625 [.0230 - .0246]

3M
Electronic Solutions Division
Interconnect Solutions
http://www.3Mconnector.com

3M is a trademark of 3M Company.
For technical, sales or ordering information call
800-225-5373

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

3M Electronics Solutions Division
6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3Mconnector.com

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
RIA-2217B-E
3M is a trademark of 3M Company.