

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Triad Magnetics N-7MG

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>





POWER TRANSFORMER CHASSIS MOUNT : Autotransformer

N-7MG

Electrical Specifications (@25°C)

- 1. Maximum Power: 600 VA
- 2. Input Voltage: 230 V, 50 / 60 Hz
- 3. Output Voltage: 115V + 5%
- 4. Full Secondary Load: 5.22 Amps RMS

Description:

The N-7MG is part of the line of Auto-Transformers that are single winding transformers in which the secondary coil is a fraction of the entire winding for voltage step-down. This causes part of the power to be transferred conductively through the windings, rather than all of the power being transferred by induction.

Safety:

These units are designed with 1500V isolation between the winding and the core. Materials and construction are rated for Class B insulation system.


Dimensions: Unit: In inches

А	В	С	D	E
4.625	3.937	5.00	3.00	3.875

Weight: 12.0 lbs

Mounting Holes: .203 x .375 Cord: 6 ft. long, Plug NEMA 6-15P, Socket NEMA 5-15R

Schematic:



RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

Web: www.TriadMagnetics.com
Phone 951-277-0757
Fax 951-277-2757

460 Harley Knox Blvd. Perris, California 92571



