

Excellent Integrated System Limited

Stocking Distributor





Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[HW02505000J0G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
HWxx50x000J0G	5.08 mm



Material:

- Item@Top body:Thermoplastic (UL94V-0)
- Item@Bottom body:Thermoplastic (UL94V-0)
- Item@Terminal lever:Thermoplastic (UL94V-0) Orange(RAL2011/P)
- Item@Spring clamp:Stainless Steel
- Item@Female contact:PhBz (CuSn) Tin plated

Electrical cULus

- Voltage rating: 300V
- Current rating: 10A
- Solid wire(AWG):12-26
- Stranded wire(AWG):12-26
- Wire strip length:8-9mm
- Withstanding Voltage:1.6KV
- Operating temperature:-40°C to +115°C
- Safety Approval: cULus

N=Number of poles
Dim A=N×5.08
Dim B=(N-1)×5.08

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.25
13P-18P	±0.30
19P-24P	±0.40

PART NO.: HW xx 50 x 0 00J0 G

Solid block	No. of poles	Color	RoHS compliant (lead<4%) In copper Alloy
0	2	Black (RAL9005)	
1	2	Red (RAL3001/D)	
2	3	Orange(RAL2011/P)	
3	4	Yellow(RAL1018/A)	
4	5	Green(RAL6018/T)	
5	6	Blue (RAL5015/A)	
6	8	Grey(RAL7035/D)	
7	9	White(RAL1102)	
8	24	Green(RAL6018/U)	

mat'l. code	surface	tolerance	projection	product family
ASME Y14.5	ASME Y14.5	ASME Y14.5	MM	TERMINAL BLOCK
lt r ecn no dr date	tolerances unless otherwise specified	angles	scale	title
	X.±0.5	X'±1°		TERMINAL BLOCK
	X.X±0.3			SPRING CLAMP,PLUGGABLE PLUG,
	X.XX±0.1			CONTACT ON DOWN SIDE
dr EVIN ZHONG 051514				dwg no
enr EVIN ZHONG 051514				sheet 1 of 1
chr HANKE FENG 051514				size
appd SHI JUN 051514				A4
sheet index	revision sheet	A		type
		1		CUSTOMER Drawing