

Excellent Integrated System Limited

Stocking Distributor




Click to view price, real time Inventory, Delivery & Lifecycle Information:

[FCI](#)
[V502315000J0G](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

PRODUCT NUMBER	PITCH
V5xx31x000J0G	3.81mm



- Material:
- Item (a) Clamp: Brass Ni plated
 - Item (b) Pin: Brass, Tin plated.
 - Item (c) Terminal screw: Steel Zinc plating
 - Item (d) Terminal housing: Thermoplastic (UL94 V-0)
 - Item (e) Terminal cover: Thermoplastic (UL94 V-0)

- Electrical: cULus
- Voltage rating: 300V
- Current rating: 8A
- Wire range:
- Solid wire(AWG): 14-28
- Stranded wire(AWG): 14-28
- Torque(Lb-In): 2.17
- Screw:M2
- Wire strip length:6 mm
- Withstanding Voltage:1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus

N = Number of poles
 Dim A = $N \times 3.81 + 1.39$
 Dim B = $(N - 1) \times 3.81$
 Dim C = $N \times 3.81 + 5.19$
 Dim D = $N \times 3.81 + 10.39$

Poles	Tolerance
2-6p	± 0.15
7-12p	± 0.20
13-18p	± 0.30
19-24p	± 0.35

PART NO.: V5 xx 31 x 0 00J0 G

Color	RoHS compliant (lead<4%) In copper Alloy
0 Black (RAL9005)	
2 Red (RAL3001/D)	
3 Orange(RAL2011/P)	
4 Yellow(RAL1018/A)	
5 Green(RAL6018/T)	
6 Blue (RAL5015/A)	
8 Grey(RAL7035/D)	
9 White(RAL1102)	
C Green(RAL6018/U)	

[illegible]