

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[333-31803](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

2.1

Insulation Products

Heat Shrinkable Tubing



**Heat Shrinkable Tubing 3:1 flexible and transparent**

- TF34

**Features and Benefits**

This flexible, halogen free tubing provides good insulation, while the clear colour allows excellent visibility of the substrate below. For general purpose applications, bundling and jacketing of cables where visual inspection is required.



TF34 transparent tubing with 3:1 shrink ratio allowing for a wider range of application.

**Cut lengths available on request. Please contact us!**

Material Data

Material	<b>Polyolefin, cross-linked (POX)</b>
Colour	<b>Transparent (CL)</b>
Shrink Ratio	<b>3:1</b>
Operating Temperature	<b>-55 °C to +135 °C</b>
Minimum Shrink Temperature	<b>+110 °C</b>
Longitudinal change after shrinkage	<b>-5% max.</b>
Dielectric Strength	<b>46 kV/mm</b>



Technical Table

Article-No.	Type	Supplied Ø D	Recov. Ø d	Wall (WT) nom.	Reel Length (m)
333-30153	<b>TF34-1.5/0.5</b>	1.5	0.5	0.50	30
333-30303	<b>TF34-3/1</b>	3.0	1.0	0.50	30
333-30603	<b>TF34-6/2</b>	6.0	2.0	0.70	30
333-30903	<b>TF34-9/3</b>	9.0	3.0	0.80	30
333-31203	<b>TF34-12/4</b>	12.0	4.0	0.85	30
333-31803	<b>TF34-18/6</b>	18.0	6.0	1.00	30
333-32403	<b>TF34-24/8</b>	24.0	8.0	1.20	30
333-34003	<b>TF34-40/13</b>	40.0	13.0	1.25	30

All dimensions in mm. Subject to technical changes.